



AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report(s). This authorization also applies to the Multiple Listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The Certification Mark(s) may be applied only at the location of the Party Authorized to Apply Mark.

Applicant: CEADESIGN S.R.L.
 Via Brenta, 8 - 36020 Pove Del Grappa (Vicenza)
 Pianezze (VI), Pianezze (VI) 36060
 Italy

Contact: Silvia Mariotto

Phone: 39 0424 566484

Email: silvia.mariotto@ceadesign.it

Party Authorized to Apply Mark: See following page(s)

Evaluation Center: Intertek (Lachine)

Client Number: 284776

Authorized By: 
 Jean-Philippe Kayl, Director of Certification

Intertek Testing Services NA, Inc.
 545 E. Algonquin Road, Ste H., Arlington Heights, IL 60005 USA
 Phone: 847-439-5667 Fax: 847-439-7320



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Testing Standard(s):	EPA WaterSense Version 1.0 High Efficiency Lavatory Faucet Specification (2007), CSA B125.1 (2012), ASME A112.18.1 (2012)
Product:	CEADESIGN Srl s. u. WaterSense Lavatory Faucets

ATM for Report: G102395382

ATM Issue Date: 10/16/2019

Listing Section(s): PLUMBING FITTINGS & ACCESSORIES

CSI Code(s): 22 30 00 Plumbing Equipment

Description:

Manufacturer Name: CEADESIGN Srl. s. u.

Brand Name: CEA

Certification Date: November 29, 2016

Product Marketing: Yes (for all models)

Maximum Rated Flow Rate: 1.5 GPM (for all models)

Type: Faucets (for all models)

WaterSense Model List

SPOUTS/TAP/FAUCETS

Family Name	Model Number	Description
BAR	BAR14	Wall mounted hydroprogressive mixer with spout L. 105 mm, horizontally assembled
BAR	BAR16	Wall mounted hydroprogressive mixer with spout L. 155 mm, horizontally assembled
BAR	BAR17	Wall mounted hydroprogressive mixer with spout L. 105 mm
BAR	BAR18	Wall mounted hydroprogressive mixer with spout L. 155 mm
BAR	BAR28	Three-hole mixer with spout H. 115 mm
BAR	BAR29	Three-hole mixer with spout H. 115 mm
BAR	BAR30	Deck mounted hydroprogressive mixer with spout
CARTESIO	CAR01	Deck mounted mixer with swivelling spout H. 340 mm
CARTESIO	CAR09	Wall mounted mixer with spout L. max. 245 mm
CARTESIO	CAR10	Wall mounted mixer with spout L. max. 200 mm
CARTESIO	CAR14	Wall mounted spout L. 200 mm
CARTESIO	CAR24	Three-hole mixer with swivelling spout H. 280 mm
FRE	FRE06	Deck mounted swivelling spout with undertop optional fixing
FRE	FRE52	Wall mounted spout L. max. 170 mm
GIOTTO	GIO10	Wall mounted set of 2 individual taps with spout L. 120 mm
GIOTTO	GIO11	Wall mounted set of 2 individual taps with spout L. 170 mm
GIOTTO	GIO16	Three-hole mixer with swivelling spout H. 240 mm
GIOTTO	GIO17	Three-hole mixer with swivelling spout H. 240 mm
GIOTTO	GIO18	Wall mounted hydroprogressive mixer with spout L. 120 mm
GIOTTO	GIO19	Wall mounted hydroprogressive mixer with spout L. 170 mm
GIOTTO	GIO21	Two-hole hydroprogressive mixer with swivelling spout H. 240 mm
GIOTTO	GIO42	Wall mounted set of 2 individual taps with spout L. 220 mm
GIOTTO	GIO44	Wall mounted hydroprogressive mixer with spout L. 220 mm
INNOVO	INV01	Deck mounted mixer with swivelling spout for gush flow H. 155 mm, opening in cold water
INNOVO	INV10	Wall mounted mixer with spout L. max. 110 mm
INNOVO	INV11	Wall mounted mixer with spout L. max. 185 mm
INNOVO	INV12	Wall mounted mixer with spout L. max. 215 mm
INNOVO	INV30	Wall mounted set of 2 individual taps with spout L. max. 110 mm

INNOVO	INV31	Wall mounted set of 2 individual taps with spout L. max. 185 mm
INNOVO	INV32	Wall mounted set of 2 individual taps with spout L. max. 215 mm
INNOVO	INV40	Two-hole mixer with swivelling spout H. 245 mm
INNOVO	INV42	Two-hole mixer with swivelling spout H. 360 mm
INNOVO	INV43	Three-hole mixer with swivelling spout H. 240 mm
INNOVO	INV45	Three-hole mixer with swivelling spout H. 360 mm
MILO360	MIL106	Wall mounted mixer with spout L. max. 215 mm
MILO360	MIL107	Wall mounted set of 2 individual taps with spout L. max. 215 mm
MILO360	MIL16	Deck mounted mixer H. 155 mm
MILO360	MIL34	Wall mounted mixer with spout L. max. 110 mm
MILO360	MIL35	Wall mounted mixer with spout L. max. 185 mm
MILO360	MIL37	Wall mounted set of 2 individual taps with spout L. max. 110 mm
MILO360	MIL38	Wall mounted set of 2 individual taps with spout L. max. 185 mm
MILO360	MIL46	Wall mounted spout L. max. 185 mm
MILO360	MIL47	Wall mounted adjustable spout L. max. 165 mm
MILO360	MIL74	Two-hole mixer with swivelling spout H. 130 mm
MILO360	MIL75	Two-hole mixer with swivelling spout H. 190 mm
MILO360	MIL76	Two-hole mixer with swivelling spout H. 280 mm
MILO360	MIL77	Three-hole mixer with swivelling spout H. 130 mm
MILO360	MIL78	Three-hole mixer with swivelling spout H. 195 mm
MILO360	MIL79	Three-hole mixer with swivelling spout H. 280 mm
ZIQQ	ZIQ10	Three-hole mixer with swivelling spout H. 240 mm
ZIQQ	ZIQ11	Three-hole mixer with swivelling spout H. 240 mm
ZIQQ	ZIQ12	Three-hole mixer with swivelling spout H. 240 mm
ZIQQ	ZIQ26	Wall mounted hydroprogressive mixer with spout L. 120 mm
ZIQQ	ZIQ27	Wall mounted hydroprogressive mixer with spout L. 170 mm
ZIQQ	ZIQ29	Wall mounted hydroprogressive mixer with spout L. 120 mm
ZIQQ	ZIQ30	Wall mounted hydroprogressive mixer with spout L. 170 mm
ZIQQ	ZIQ58	Wall mounted hydroprogressive mixer with spout L. 220 mm
ZIQQ	ZIQ59	Wall mounted hydroprogressive mixer with spout L. 220 mm

Party(s) Authorized by Manufacturer To Apply Mark:
None

Party(s) Authorized by Other Parties To Apply Mark:
None



AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report(s). This authorization also applies to the Multiple Listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The Certification Mark(s) may be applied only at the location of the Party Authorized to Apply Mark.

Applicant: CEADESIGN S.R.L.
 Via Brenta, 8 - 36020 Pove Del Grappa (Vicenza)
 Pianezze (VI), Pianezze (VI) 36060
 Italy

Contact: Silvia Mariotto

Phone: 39 0424 566484

Email: silvia.mariotto@ceadesign.it

Party Authorized to Apply Mark: See following page(s)

Evaluation Center: Intertek (Lachine)

Client Number: 284776

Authorized By: 
 Jean-Philippe Kayl, Director of Certification

Intertek Testing Services NA, Inc.
 545 E. Algonquin Road, Ste H., Arlington Heights, IL 60005 USA
 Phone: 847-439-5667 Fax: 847-439-7320



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Testing Standard(s):	CSA B125.1 (2012), ASME A112.18.1 (2012), EPA WaterSense® Specification for Showerheads (2010)
Product:	CEADESIGN Srl s. u. WaterSense Showerheads

ATM for Report: G102395382

ATM Issue Date: 10/16/2019

Listing Section(s): PLUMBING FITTINGS & ACCESSORIES

CSI Code(s): 22 30 00 Plumbing Equipment

Description:

Manufacturer Name: CEADESIGN Srl. s. u.

Brand Name: CEA

Certification Date: November 29, 2016

Product Marketing: Yes (for all models)

Maximum Rated Flow Rate: 2.00 GPM (for all models)

Minimum Rated Flow Rate (at 45 psi): 1.50 GPM (for all models)

WaterSense Model List

SHOWERHEADS

Family Name	Model Number	Description
FRE	FRE11	Square adjustable shower head L. 200 mm, with transparent silicone nozzles
FRE	FRE12	Round adjustable shower head ø 200 mm, with transparent silicone nozzles
NEUTRA	NEU39	Adjustable rain jet shower head with Delrin® end and silicone nozzles

Party(s) Authorized by Manufacturer To Apply Mark:

None

Party(s) Authorized by Other Parties To Apply Mark:

None